

PALLAS

Pallas product is a Thermo-E-glass fabric with an inorganic coating on both sides in order to increase the antislip properties and the heat resistancy.

This special coating provides a temperature resistance of approx. 700 °C (with a short time peak resistance of even 750 °C). Pallas is supplied as welding blankets made size, in standard sizes or on rolls of 25 meters length. Pallas is ideal to be used cut from the roll, as the cutting edges do not unravel.

Technical data

Test	Standard*	
1. Binding	DIN 61 101 - 1	Atlas 1/7
2. Width	DIN EN 1773	1000 mm
3. Thickness	DIN EN ISO 5084	0,7 mm
4. Mass	DIN 53 854	680 g/m ²
5. Number of threads -warp -weft	DIN EN 1049 - 2	16,0 yarns/cm 15,0 yarns/cm
6. Yarn count - warp - weft	DIN 53 830 - 3	68 tex x 3 68 tex x 3
7. Filament diameter - warp - weft	DIN 53 811	9 µm 9 µm
8. Tensile strength - warp - weft	DIN 53 857 - 1	> 4000 N/5 cm > 3000 N/5 cm

Subjects to tolerances



CEPRO International BV verkoopt en levert al haar goederen uitsluitend onder toepasselijkheid van haar algemene leverings- en betalingsvoorwaarden, welke op uw verzoek kosteloos worden toegezonden.